

Industrial Plasma Cutter

RJ-1530



Feature

- Reasonable platform design, 10mm thickness steel plates fixed on the table covered by cast sheath with spikes. Steel plates will not be damaged even under raging flame.
- The level difference of whole double-decked platform remains in 0-1.5mm.
- Panasonic servo motor, Taiwan servo reducer device and high accuracy rack gear transmission.
- Starfire control system made in Sino-US joint venture and Germany Design Software FastCAM with auto material saving function.
- American Cut-Master plasma power supply or American Hypertherm together with high sensitive arc pressure adjuster.
- Self-adjusting to choose the best distance between plasma gun and working piece automatically in order to ensure cutting accuracy.

| | |
|---|---|
| Model | RJ-1530 |
| Processing Materials | Iron, aluminum, galvanized sheet, white steel plate, titanium plate |
| Working Area | 1500mm x 3000mm |
| Motive System | Japan Panasonic servo motor with speed reducer |
| Cutting Speed | 0-8000mm/min |
| Moving Speed | 0-50000mm/min |
| Cutting Thickness (Cutmaster Power Generator) | (60A)3-8mm (120A)3-16mm (200A)3-25mm |
| Power | 8.5KW-10.5KW |
| Input Voltage | 3 phase 380V |
| Power Frequency | 50Hz |
| Control System | starfire system |
| Flies Transfer | USB Interface |
| Arc | Untouched Arc Striking Arc Height Adjuster(HyperCNC) |
| Packing Size | 16.83CBM |
| N .W/G .W | 1200KGS/1420KGS |

